

Product and manufacturer details	
Product Name:	<b>Texan 175 copper external spouting bracket</b>
Product Identifier:	TEXEBC-COM
Manufacturer's Name & Address	Continuous Group Ltd, 6 Yashili Drive, Pokeno 2402
Manufacturer's Email Address	<a href="mailto:cg@continuous.co.nz">cg@continuous.co.nz</a>
Manufacturer's Web Address	<a href="http://www.continuous.co.nz">www.continuous.co.nz</a>
Manufacturer's NZBN	9429034817001
Place of Manufacture	Aotearoa New Zealand
Warnings & Bans	No

### Product description

Texan 175 copper external spouting bracket (face fix or pan fix) is a spouting bracket used in the installation of Texan 175 spouting system.

**Table 1**

Component	Component - Material
CG Texan 175 External Bracket	2.50mm BMT Copper (Grade 6060,T591)

### Installation Requirements

Refer to Texan 175 copper spouting system BPIR: TEXCU-SYS:2023.v1 for full system and installation details.

### Scope of use

Texan 175 copper external spouting bracket (face fix or pan fix) is designed to fit Texan 175 spouting.

### Limitations of the use of this building product:

1. The product cannot be installed onto fascia or cladding with incompatible materials. The product cannot run-off onto incompatible materials. Material Compatibility, Contact and Run off to be adhered to in accordance with E2/AS1 Table 20, 21 & 22
2. Site locations must be evaluated in areas with high wind &/or salt &/or thermal/industrial atmospheric conditions. These types of locations may require specific engineering design (SED). Designers must consult metal supplier's information for specific durability requirements (Reference E2/AS1 table 20)

### Maintenance Requirements

*(Link to Care and Maintenance Document below under "Supporting Documentation")*

1. Inspection of the product is required every 3 months to check for buildup of residue.
2. Wash the exterior surface of the product at a minimum of every 6 months and immediately after inspection if required.

### Relevant building code clauses.

Compliance/Regulation	Detail
E2/AS1 External Moisture	Table 20
B2/AS1	Table 1: Durability Requirements of Nominated Building Element

**Texan 175 copper spouting bracket contributes to compliance by –**

***E2/AS1 Table 20: “Material Selection”***

- The product is classified as “Sheltered” and material selection shown in Table 1 of this BPIR meets the requirements of table 20 for exposure Zones B,C, D & E for “Copper” and “uPVC” materials.

***B2/AS1 Table 1: Durability Requirements of Nominated Building Element- requires external gutters to have a durability of 5 Years.***

- This gutter product is provided with a 10 year warranty if the maintenance conditions are met.

**Supporting documentation**

The following additional documentation supports the above statements:

Document name	Weblinks
Texan 175mm Brochure & Specification Document	<a href="#">Texan Spouting Brochure and Specification 2021.pdf</a>
Maintenance Document	<a href="#">Continuous Group Maintenance Document.pdf</a>
Material Compatibility Selection	<a href="#">Continuous Group Material Compatibility - Material Selection v1.pdf</a>
Material Compatibility in Contact	<a href="#">Continuous Group Material Compatibility - Compatibility of materials in contact v1.pdf</a>
Material Compatibility subject to Run Off	<a href="#">Continuous Group Material Compatibility - Compatibility of materials subject to run off v1.pdf</a>
Warranty Document	<a href="#">Continuous Group Warranties</a>